DEPENDENT	RESU	RVEY	OF	THE	NORTH	BOUNDARY	,
ய ၁	6 N	D (58 T	, ו	ALL MALL	$\Delta C \Delta V H$	

T37N R58E 2 S 3 5 T36N 1976 set a steel fence post, 5½ ft. long, 2¼ ins. in the ground, alongside the aluminum post. 80.42 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the cor. of secs. 5, 6, 32 and 37. Set an aluminum post, 30 ins. long, 2½ ins. diam., 2¼ ins in the ground, with aluminum cap mkd. T37N R58E 8 37 S 32 S 6 S 5 T36N 1977 set a steel fence post, 5½ ft. long, 2½ ins. in the ground, alongside the aluminum post. N. 89° 50' W., bet. secs. 6 and 37. Over rolling land, covered with sagebrush. Now rolling land, covered with sagebrush. Point for the ½ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the ½ sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, ¼ ft. base to top, with aluminum cap mkd. T37N R58E 2 S 37 5 S 37 T36N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E., executed under Group No. 521.		,
set a steel fence post, 5½ ft. long, 2¼ ins. in the ground, alongside the aluminum post. 80.42 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the cor. of secs. 5, 6, 32 and 37. Set an aluminum post, 30 ins. long, 2½ ins. diam., 2¼ ins in the ground, with aluminum cap mkd. **T37N R58E** **S 37 \ S 32 **S 6 S 5 **T36N** 1977 set a steel fence post, 5½ ft. long, 2¼ ins. in the ground, alongside the aluminum post. N. 89° 50' W., bet. secs. 6 and 37. Over rolling land, covered with sagebrush. Point for the ½ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the ½ sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, ¼ ft. base to top, with aluminum cap mkd. **T37N R58E** ½ \$ 37 ½ \$ 5 6 **T36N** 1977 ¼1.00 Ridge, bears NNE. and SSW. **Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		
set a steel fence post, 5½ ft. long, 2¼ ins. in the ground, alongside the aluminum post. 80.42 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the cor. of secs. 5, 6, 32 and 37. Set an aluminum post, 30 ins. long, 2½ ins. diam., 2¼ ins in the ground, with aluminum cap mkd. 137N R58E S 37 S 32 S 6 S 5 T36N 1977 set a steel fence post, 5½ ft. long, 2¼ ins. in the ground, alongside the aluminum post. N. 89° 50' W., bet. secs. 6 and 37. Over rolling land, covered with sagebrush. Point for the % sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the % sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, ¼ ft. base to top, with aluminum cap mkd. 137N R58E % 8 37 % 8 6 T36N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains 5. 80.17 The cor. of Tps. 36 and 37 W., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		<u>s 32</u>
set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the aluminum post. 80.42 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the cor. of secs. 5, 6, 32 and 37. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins in the ground, with aluminum cap mkd. 137N R58E 8 37 8 32 8 6 3 5 136N 1977 set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the aluminum post. N. 89° 50' W., bet. secs. 6 and 37. Over rolling land, covered with sagebrush. Point for the 4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the 4 sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd. 137N R58E 4 8 37 8 6 136N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		· /
set a steel fence post, 5½ ft. long, 2¼ ins. in the ground, alongside the aluminum post. 80.42 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the cor. of secs. 5, 6, 32 and 37. Set an aluminum post, 30 ins. long, 2½ ins. diam., 2¼ ins in the ground, with aluminum cap mkd. \$\begin{array}{cccccccccccccccccccccccccccccccccccc		
ground, alongside the aluminum post. 80.42 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the cor. of secs. 5, 6, 32 and 37. Set an aluminum post, 30 ins. long, 2½ ins. diam., 2¼ ins in the ground, with aluminum cap mkd. T37N R58E S37 S32 S6S5 T36N 1977 set a steel fence post, 5½ ft. long, 2¼ ins. in the ground, alongside the aluminum post. N. 89° 50' W., bet. secs. 6 and 37. Over rolling land, covered with sagebrush. 40.21 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the ¼ sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, ¼ ft. base to top, with aluminum cap mkd. T37N R58E ½ S37 5 6 T36N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		1976
tionate distance; there is no remaining evidence of the original corner. This corner now refers to the cor. of secs. 5, 6, 32 and 37. Set an aluminum post, 30 ins. long, 2½ ins. diam., 2¼ ins in the ground, with aluminum cap mkd. T37N R58E S37 S 32 S 6 S 5 T36N 1977 set a steel fence post, 5½ ft. long, 2¼ ins. in the ground, alongside the aluminum post. N. 89° 50' W., bet. secs. 6 and 37. Over rolling land, covered with sagebrush. Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the ¼ sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, ¼ ft. base to top, with aluminum cap mkd. T37N R58E ½ S 37 S 6 T36N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		
in the ground, with aluminum cap mkd. T37N R58E S 37 S 32 S 618 5 T36N 1977 set a steel fence post, 5½ ft. long, 2½ ins. in the ground, alongside the aluminum post. N. 89° 50' W., bet. secs. 6 and 37. Over rolling land, covered with sagebrush. Point for the ½ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the ½ sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, ¼ ft. base to top, with aluminum cap mkd. T37N R58E ½ S 37 ½ S 6 T36N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,	80,42	tionate distance; there is no remaining evidence of the original corner. This corner now refers to the cor. of
S 37 \ S 32 S 6 S 5 T36N 1977 set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the aluminum post. N. 89° 50' W., bet. secs. 6 and 37. Over rolling land, covered with sagebrush. 40.21 Point for the ½ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the ½ sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, ½ ft. base to top, with aluminum cap mkd. T37N R58E ½ S 37 T36N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
ground, alongside the aluminum post. N. 89° 50' W., bet. secs. 6 and 37. Over rolling land, covered with sagebrush. Point for the 4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the 4 sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd. T37N R58E 1/4 S 37 T36N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,	-	<u>s 37 \ s 32</u> s 6 s 5 ⊤36N
Over rolling land, covered with sagebrush. Point for the 4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the 4 sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd. T37N R58E 4 S 37 5 6 T36N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		
Point for the ½ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the ½ sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd. T37N R58E ½ \$ 37 / \$ 6 / \$ 736N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		N. 89° 50' W., bet. secs. 6 and 37.
tionate distance; there is no remaining evidence of the original corner. This corner now refers to the ½ sec. cor. of secs. 6 and 37. Set an aluminum post, 30 ins. long, 6 ins. in the ground to solid rock and in a mound of stone, ¼ ft. base to top, with aluminum cap mkd. T37N R58E ½ S 37/S 6 T36N 1977 41.00 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, ½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		Over rolling land, covered with sagebrush.
to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd. T37N R58E \[\frac{S}{37} \] \frac{S}{5} \frac{6}{T36N} \] 1977 Ridge, bears NNE. and SSW. Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2\frac{1}{2} ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,	40.21	tionate distance; there is no remaining evidence of the original corner. This corner now refers to the 4 sec.
1977 41.00 Ridge, bears NNE. and SSW. 58.00 Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		to solid rock and in a mound of stone, 4 ft. base to
14 S 37 S 6 T36N 1977 41.00 Ridge, bears NNE. and SSW. 58.00 Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		ТЗ7N R58E
T36N 1977 41.00 Ridge, bears NNE. and SSW. 58.00 Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		
1977 41.00 Ridge, bears NNE. and SSW. 58.00 Draw, drains S. 80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		
Ridge, bears NNE. and SSW. Draw, drains S. The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		130N
Draw, drains S. The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,		1977
80.17 The cor. of Tps. 36 and 37 N., Rs. 57 and 58 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,	41.00	Ridge, bears NNE. and SSW.
mented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,	58.00	Draw, drains S.
mented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,	80.17	The cor of Ths. 36 and 37 N. Rs. 57 and 58 E. monu-
1		mented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E.,