

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 36 N., R. 58 E., MDM, NEVADA

<p>CHAINS 39.98</p>	<p>The cor. of secs. 23, 24, 25 and 26, monumented with the remains of a willow post, loosely set in a mound of earth alongside a steel fence post, 6 ft. long, firmly set and exposed 4½ ft. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R58E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">1976</p> <p>reset the remains of the original wooden post and steel fence post, 24 ins. in the ground, alongside the aluminum post.</p> <p>From this corner, a well with 7 in. casing, bears S. 73° 19' W., 4.97 chs. dist.</p>	
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of T. 36 N., R. 59 E., executed concurrently under this same group.</p> <p>N. 89° 41' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land, covered with crested wheatgrass.</p>	
<p>1.10</p>	<p>Draw, drains NNE.</p>	
<p>39.89</p>	<p>Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R58E ¼ S 24 S 25</p> <p style="text-align: center;">1976</p> <p>set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the aluminum post.</p>	
<p>79.78</p>	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>N. 1° 25' E., bet. secs. 23 and 24.</p> <p>Over gently rolling land, covered with crested wheatgrass and sagebrush.</p>	