

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES  
T. 36 N., R. 58 E., MDM, NEVADA

CHAINS 40.16	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 29, monumented with a wooden stake, 1x2x16 ins. long, firmly set and exposed 4 ins. above ground. This position is harmoniously related to other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R58E <math>\frac{1}{4}</math> <math>\frac{S\ 20}{S\ 29}</math> 1976</p> <p>reset the wooden stake and set a steel fence post, <math>5\frac{1}{2}</math> ft. long, 24 ins. in the ground, alongside the aluminum post.</p> <hr/> <p>S. <math>89^{\circ} 51'</math> W., beginning new measurement.</p> <p>Over gently rolling land, covered with sagebrush.</p>	
35.00	Draw, drains SE.	
40.24	The cor. of secs. 19, 20, 29 and 30.	
40.65	<p>N. <math>89^{\circ} 21'</math> W., bet. secs. 19 and 30.</p> <p>Over gently rolling land, covered with sagebrush.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T36N R58E <math>\frac{1}{4}</math> <math>\frac{S\ 19}{S\ 30}</math> 1976</p> <p>set a steel fence post, <math>5\frac{1}{2}</math> ft. long, 24 ins. in the ground, alongside the aluminum post.</p>	
60.50	Draw, drains S.	
80.79	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E., executed under Group No. 521.	