

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 36 N., R. 58 E., MDM, NEVADA

CHAINS	
	<div>T36N R58E</div> <div><div><div><div><div></div><div>S 18</div></div><div><div>¼</div><div>S 19</div></div></div></div></div> <div>1976</div> <div>set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the aluminum post.</div>
80.38	<div>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E., executed under Group No. 521.</div>
	<div>From the cor. of secs. 17, 18, 19 and 20.</div> <div>N. 0° 26' E., bet. secs. 17 and 18.</div> <div>Over gently rolling land, covered with sagebrush.</div>
14.00	<div>Draw, drains SSE.</div>
34.00	<div>Spur, slopes SSE.</div>
40.10	<div>Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</div> <div><div>T36N R58E</div><div><div><div><div><div></div><div>S 18</div></div><div><div>¼</div><div>S 17</div></div></div></div></div><div>1976</div><div>set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the aluminum post.</div></div>
77.00	<div>Draw, drains NE.</div>
80.20	<div>The cor. of secs. 7, 8, 17 and 18, monumented with the remains of a square willow post, 2x2x14 ins. long, loosely set in a mound of earth.</div> <div>At the corner point</div> <div>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</div> <div><div>T36N R58E</div><div><div><div><div><div></div><div>S 7</div></div><div><div>S 8</div><div>S 18</div></div></div></div><div><div>S 17</div><div>S 17</div></div></div><div>1976</div><div>reset the remains of the original wooden post and set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the aluminum post.</div></div>