## DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES T. 36 N., R. 58 E., MDM, NEVADA

CHAINS	N. 87° 58' W., beginning new measurement.
	Over gently rolling land, covered with sagebrush.
40.17	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 57 E., executed under Group No. 521.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0° 04' W., bet. secs. 7 and 8.
	Over rolling land, covered with sagebrush.
40.18	The 4 sec. cor. of secs. 7 and 8, monumented with the remains of a square willow post, lxlxl7 ins. long, loosely set in a mound of earth.
<i>2.</i>	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T36N R58E
	s 7 s 8
	1976
	reset the remains of the original wooden post and set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the aluminum post.
	N. 0° 20' E., beginning new measurement.
	Over rolling land, covered with sagebrush.
21.50	Draw, drains E.
40.32	Powerline, bears E. and W.
40.46	The cor. of secs. 5, 6, 7 and 8, monumented with the remains of a willow post, lxlx6 ins. long, loosely set in a mound of earth.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T36N R58E S 6 S 5 S 7 S 8
	1976
	reset the remains of the original wooden post and set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the aluminum post.
	1