

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 37 N., R. 58 E., MDM, NEVADA

CHAINS		
	<p>N. 0° 37' E., beginning new measurement.</p> <p>Over gently rolling land, covered with sagebrush.</p> <p>10.00 Ridge, bears NE. and SW.</p> <p>23.30 Trail road, bears E. and W.</p> <p>40.05 The cor. of secs. 1, 6, 7 and 12, monumented with the decayed remains of a willow post, with an iron pipe, 2 ins. in diam., firmly set and exposed 10 ins. above ground, with top mkd.</p>	
	<p style="text-align: center;">T37N R58E R59E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1968</p> <p>with a steel fence post, firmly set and exposed 3½ ft. above ground, alongside the iron pipe.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R58E R59E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1976</p> <p>reset the remains of the original wooden post, invert the iron pipe and reset the steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p>	
40.47	<p>N. 0° 01' E., bet. secs. 1 and 6.</p> <p>Over gently rolling land, covered with sagebrush.</p> <p>The ¼ sec. cor. of secs. 1 and 6, monumented with the decayed remains of a willow post, loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R58E R59E ¼ S 1 S 6</p> <p style="text-align: center;">1976</p> <p>reset the remains of the original wooden post and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p>	