

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 N., R. 58 E., MDM, NEVADA

CHAINS		
	<p>Set an iron post, 28 ins. long, 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T38N R58E $\frac{1}{4}$ $\frac{S\ 32}{S\ 5}$ T37N 1977</p> <p>bury the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 88° 51' W., beginning new measurement.</p> <p>Over rolling land covered with sagebrush; desc. 200 ft. over a NW. slope; along fence.</p>	
39.76	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a conglomerate stone, 1x6x6 ins., plainly mkd. with 5 notches on the E. edge, 1 groove on the W. face, firmly set in a mound of stone, with a steel fence post, firmly set alongside the mound of stone and in a fence, bearing irregularly E. and W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T38N R58E $\frac{S\ 31}{S\ 6}$ $\frac{S\ 32}{S\ 5}$ T37N 1977</p> <p>bury the original cornerstone and reset the steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
29.00	<p>N. 89° 12' W., bet. secs. 6 and 31.</p> <p>Over rolling land, covered with sagebrush; desc. 220 ft. over a W. slope, along fence.</p>	
38.92	<p>Draw, drains NE.; asc. 20 ft. over a NE. slope.</p> <p>The ¼ sec. cor. of sec. 6 and 31, monumented with a conglomerate stone, 10x8x6 ins., plainly mkd. ¼ on the N. face, with a mound of stone to the S., with a steel fence post firmly set alongside the mound of stone and in a fence, bearing E. and W.</p> <p>At the corner point</p>	