



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 58 E., MDM, NEVADA

CHAINS		
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T37N S 31 S 37 R58E</p> <p style="margin-left: 100px;">S 32</p> </div> <p style="text-align: center;">1977</p> <p>bury the original cornerstone and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
	<p>S. 88° 58' W., bet. secs. 31 and 37.</p> <p>Over rolling land, covered with sagebrush; asc. 320 ft. over an E. slope.</p>	
25.00	<p>Ridge, bears NNE. and SSW.; desc. 150 ft. over a W. slope.</p>	
39.94	<p>The ¼ sec. cor. of secs. 6 and 31, as resurveyed in 1887 by Henry Fitzhugh, U. S. Deputy Surveyor, monumented with a quartzite stone, 13x7x4 ins., plainly mkd. ¼ on the N. face, firmly set and exposed 4 ins. above ground, with a steel fence post alongside. This corner now refers to the ¼ sec. cor. of secs. 31 and 37 only.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T37N R58E ¼ S 31 S 37</p> </div> <p style="text-align: center;">1977</p> <p>bury the original cornerstone and reset the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>	
	<p>S. 89° 31' W., beginning new measurement.</p> <p>Over rolling land, covered with sagebrush.</p>	
16.00	<p>Draw, drains SE.; asc. 180 ft. over an E. slope.</p>	
40.22	<p>The cor. of secs. 31 and 37, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 57 E., executed under Group No. 521.</p>	