

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 58 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T37N R58E S 30 ¼ S 31 1976</p>
	<p>bury the original cornerstone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/>
	<p>S. 89° 27' W., beginning new measurement.</p>
	<p>Over rolling land, covered with sagebrush; asc. 30 ft. over an E. slope, along fence.</p>
3.70	<p>Spur, slopes N.; desc. 140 ft. over a W. slope.</p>
39.92	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 57 E., executed under Group No. 521.</p> <hr/>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p>
	<p>N. 0° 41' E., bet. secs. 29 and 30.</p>
	<p>Over rolling land, covered with sagebrush; desc. 40 ft. over a N. slope.</p>
5.50	<p>Draw, drains NE.; asc. 20 ft. over an E. slope.</p>
17.60	<p>Trail road, bears NW. and SSE.; desc. 10 ft. over an E. slope.</p>
21.50	<p>Draw, drains SE.; asc. 40 ft. along draw, which drains S.</p>
32.00	<p>Leave draw, bears NE.; asc. 60 ft. over a S. slope.</p>
40.52	<p>The ¼ sec. cor. of secs. 29 and 30, monumented with a trachyte stone, 17x12x8 ins., plainly mkd. ¼ on the W. face, firmly set and exposed 8 ins. above ground, with a mound of stone to the E.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T37N R58E ¼ S 30 S 29 1976</p>
	<p>bury the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: auto;"/>