

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 58 E., MDM, NEVADA

CHAINS	
	Asc. 240 ft. over a SE. slope.
68.00	Spur, slopes SW.; desc. 160 ft. over a W. slope.
80.16	The cor. of secs. 19, 20, 29 and 30.
	S. 86° 06' W., bet. secs. 19 and 30.
	Over rolling land, covered with sagebrush; desc. 70 ft. over a W. slope.
19.00	Trail road, bears NNE. and SSW.; desc. 40 ft. over a W. slope.
40.44	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T37N R58E $\frac{1}{4}$ $\frac{S\ 19}{S\ 30}$ 1976</p>
	set a steel fence post, 5 $\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.
	Desc. 60 ft. over a W. slope.
73.00	Trail road, bears ENE. and WSW.; descend 20 ft. over a W. slope.
81.54	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 57 E., executed under Group No. 521.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 1° 22' E., bet. secs. 19 and 20.
	Over rolling land, covered with sagebrush; asc. 40 ft. over a SW. slope.
6.00	Spur, slopes W.; desc. 60 ft. over a NW. slope.
18.50	Trail road, bears NE. and SW.; desc. 20 ft. over a W. slope.
25.50	Draw, drains SSW.; asc. 100 ft. over a W. slope.