

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 37 N., R. 58 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R58E ¼ <math>\frac{S\ 18}{S\ 19}</math> 1976</p> <p>set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>Desc. 100 ft. over a W. slope.</p>
48.00	Draw, drains NW.; asc. 20 ft. over a N. slope.
82.56	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 57 E., executed under Group No. 521.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 2° 30' W., bet. secs. 17 and 18.</p> <p>Over rolling land, covered with sagebrush; desc. 80 ft. over a NW. slope.</p>
9.00	Draw, drains WSW.; asc. 60 ft. over a S. slope.
15.00	Spur, slopes W.; desc. 180 ft. over a NW. slope.
35.08	<p>Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R58E ¼ S 18   S 17 1976</p> <p>set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p>
38.00	Draw, drains SW.; asc. 80 ft. over a SE. slope.
43.50	Spur, slopes SW.; asc. 20 ft. over a W. slope.
54.00	Spur, slopes W.; desc. 30 ft. over a W. slope.
61.00	Spur, slopes NW.; desc. 120 ft. over a NW. slope.
68.00	Draw, drains NW.; asc. 20 ft. over a SW. slope.