

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 37 N., R. 58 E., MDM, NEVADA

CHAINS		
	N. 86° 16' W., bet. secs. 7 and 18.	
	Over rolling land, covered with sagebrush; desc. 60 ft. over a SSW. slope.	
3.00	Draw, drains NW.; desc. 180 ft. over a NW. slope.	
33.00	Draw, drains SW.; asc. 100 ft. over a SE. slope.	
39.30	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., $\frac{1}{4}$ ins. in the ground to bedrock and in a mound of stone, $\frac{1}{4}$ ft. base to top, with brass cap mkd.	
	T37N R58E $\frac{1}{4} \frac{S \ 7}{S \ 18}$	
	1976	
	Asc. 100 ft. over a S. slope.	
57.00	Spur, slopes S.; desc. 140 ft. over a W. slope.	
80.14	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 57 E., executed under Group No. 521.	
	From the cor. of secs. 7, 8, 17 and 18.	
	N. 1° 17' E., bet. secs. 7 and 8.	
	Over rolling land, covered with sagebrush.	
12.00	Spur, slopes NW.; desc. 100 ft. over a NW. slope.	
16.00	Draw, drains SW.; asc. 220 ft. over a S. slope.	
53.68	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with a conglomerate stone, 12x12x6 ins., plainly mkd. $\frac{1}{4}$ on the W. face and firmly set in a mound of stone.	
	At the corner point	
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T37N R58E $\frac{1}{4}$ S 7   S 8	
	1976	
	bury the original cornerstone and set a steel fence post, 5 $\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.	