

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 58 E., MDM, NEVADA

CHAINS	
	<p>N. 88° 05' W., beginning new measurement.</p> <p>Over rolling land, covered with sagebrush; asc. 120 ft. over a S. slope.</p>
13.00	Spur, slopes NE.; desc. 240 ft. over a NW. slope.
39.50	The cor. of secs. 5, 6, 7 and 8.
	<hr/> <p>S. 77° 38' W., bet. secs. 6 and 7.</p>
	<p>Over rolling land, covered with sagebrush; desc. 300 ft. over a NW. slope.</p>
27.00	Draw, drains NW.; asc. 60 ft. over a NE. slope.
33.00	Spur, slopes NW.; desc. 80 ft. over a W. slope.
42.26	<p>The ¼ sec. cor. of secs. 6 and 7, monumented with a trachyte stone, 14x8x8 ins., mkd. ¼ on the N. face and firmly set in a mound of stone.</p>
	At the corner point
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T37N R58E ¼ $\frac{S \ 6}{S \ 7}$</p>
	<p style="text-align: center;">1976</p>
	<p>bury the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.</p>
	<hr/> <p>S. 89° 46' W., beginning new measurement.</p>
	<p>Over rolling land, covered with sagebrush; asc. 60 ft. over an E. slope.</p>
9.00	Spur, slopes NW.; desc. 260 ft. over a W. slope.
40.50	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 57 E., executed under Group No. 521.</p>