

TOWNSHIP 36 NORTH, RANGE 59 EAST, MDM, NEVADA

| CHAINS | | | | | | | | | | | | | | | | | |
|--------|---|------|--|-------|--|--|---|--|---------------------------|--|------|--|---|--|---|-------|---|
| | <div>DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 59 EAST, MOUNT DIABLO MERIDIAN, NEVADA</div> <div>Reestablishment of the Survey Executed by C.C. Tracy, U.S. Deputy Surveyor, in 1868.</div> <div>The standard corner of secs. 32 and 33, T. 36 N., R. 59 E., monumented with a rebar, ½ in. diam., 14 ins. long, firmly set and exposed 1 in. above ground in a fence bearing E. and W. This position is harmoniously related to other existing original corners and is accepted as the best available evidence of the position of the original corner.</div> <div>At the corner point</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</div> <div>SC T36N R59E S 32 S 33</div> <div>1976</div> <div>reset the rebar alongside the iron post.</div> <div>N. 89° 51' W., along the S. bdy. of sec. 32.</div> <div>Over gently rolling land, through crested wheatgrass; along fence.</div> <tr><td>5.90</td><td>Fence corner, from which fences bear N., E., and W.; along fence.</td></tr> <tr><td>40.27</td><td>Point for the standard ¼ sec. cor. of sec. 32, determined longitudinally at proportionate distance and latitudi- nally in a fence bearing E. and W.; there is no remain- ing evidence of the original corner.</td></tr> <tr><td></td><td>Set an iron post, 28 ins. long, 2½ ins. diam, 24 ins. in the ground, with brass cap mkd.</td></tr> <tr><td></td><td>SC T36N R59E ¼ S 32</td></tr> <tr><td></td><td>1976</td></tr> <tr><td></td><td>N. 89° 58' W., beginning new measurement.</td></tr> <tr><td></td><td>Over gently rolling land, through crested wheatgrass; along fence.</td></tr> <tr><td>40.27</td><td>Point for the standard corner of secs. 31 and 32, deter- mined longitudinally at proportionate distance and latitudinally in a fence bearing E. and W.; there is no remaining evidence of the original corner.</td></tr> | 5.90 | Fence corner, from which fences bear N., E., and W.; along fence. | 40.27 | Point for the standard ¼ sec. cor. of sec. 32, determined longitudinally at proportionate distance and latitudi- nally in a fence bearing E. and W.; there is no remain- ing evidence of the original corner. | | Set an iron post, 28 ins. long, 2½ ins. diam, 24 ins. in the ground, with brass cap mkd. | | SC T36N R59E ¼ S 32 | | 1976 | | N. 89° 58' W., beginning new measurement. | | Over gently rolling land, through crested wheatgrass; along fence. | 40.27 | Point for the standard corner of secs. 31 and 32, deter- mined longitudinally at proportionate distance and latitudinally in a fence bearing E. and W.; there is no remaining evidence of the original corner. |
| 5.90 | Fence corner, from which fences bear N., E., and W.; along fence. | | | | | | | | | | | | | | | | |
| 40.27 | Point for the standard ¼ sec. cor. of sec. 32, determined longitudinally at proportionate distance and latitudi- nally in a fence bearing E. and W.; there is no remain- ing evidence of the original corner. | | | | | | | | | | | | | | | | |
| | Set an iron post, 28 ins. long, 2½ ins. diam, 24 ins. in the ground, with brass cap mkd. | | | | | | | | | | | | | | | | |
| | SC T36N R59E ¼ S 32 | | | | | | | | | | | | | | | | |
| | 1976 | | | | | | | | | | | | | | | | |
| | N. 89° 58' W., beginning new measurement. | | | | | | | | | | | | | | | | |
| | Over gently rolling land, through crested wheatgrass; along fence. | | | | | | | | | | | | | | | | |
| 40.27 | Point for the standard corner of secs. 31 and 32, deter- mined longitudinally at proportionate distance and latitudinally in a fence bearing E. and W.; there is no remaining evidence of the original corner. | | | | | | | | | | | | | | | | |