

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 36 N., R. 59 E., MDM, NEVADA

CHAINS

T37N
R58E R59E
S 36 | S 31
S 1 | S 6
T36N

1976

reset the original wooden post, the pine post, and the steel fence post, 24 ins. in the ground, alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed
by C. C. Tracy, U.S. Deputy Surveyor, in 1869.

The cor. of secs. 27, 28, 33 and 34, monumented with a juniper post, 4 ins. square, 20 ins. long, firmly set and exposed 4 ins. above ground. This position is harmoniously related to other existing original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R59E
S 28 | S 27
S 33 | S 34

1976

reset the wooden post and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.

N. 2° 05' E., between secs. 27 and 28.

Over nearly level land, through native grasses and sagebrush.

40.64

Point for the ¼ sec. cor. of secs. 27 and 28, determined longitudinally at proportionate distance and latitudinally in an E. and W. fence; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R59E
¼
S 28 | S 27

1976

From this corner, the corner of fences bears W., 5.77 chs. dist., from which fences bear N. 9½° E., W., and E.