

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 37 N., R. 59 E., MDM, NEVADA

CHAINS  
19.17 Interstate 80, eastbound lane, bears N. 57 3/4° E. and S. 57 3/4° W.  
22.99 Interstate 80, westbound lane, bears N. 57 3/4° E. and S. 57 3/4° W.  
27.80 Fence, bears N. 56 3/4° E. and S. 56 3/4° W.  
40.10 Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T37N R59E  
S 31  
1/4 S 6  
T36N

1976

set a steel fence post, 5 1/2 ft. long, 22 ins. in the ground, alongside the iron post.

78.03 The cor. of Tps. 36 and 37 N., Rs. 58 and 59 E., monumented with an aluminum post, 2 1/2 ins. diam., firmly set and exposed 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 59 E., executed concurrently under this same group.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 37 N., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
C.C. Tracy, U.S. Deputy Surveyor,  
in 1868.

The cor. of secs. 25, 30, 31 and 36, determined at the cor. of fences, from which fences bear N., S. and W. The cor. of fences is locally recognized as the cor. and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T37N  
R59E R60E  
S 25 | S 30  
S 36 | S 31

1977