

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 54 E., MDM, NEVADA

CHAINS	
	<p>N. 89° 44' W., beginning new measurement.</p> <p>Over mountainous land; asc. 320 ft. over an E. slope.</p> <p>37.15 The closing cor. of secs. 5 and 6, monumented with a basalt stone, 14x10x6 ins., plainly mkd. with 5 notches on E. edge, 1 notch on W. edge, and CC on the S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T41N R54E</p> <p>S 32</p> <hr style="width: 50px; margin: 0 auto;"/> <p>C C</p> <p>S 6 S 5</p> <p>T40N R54E</p> </div> <p>1976</p> <p>bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>Ascend 80 ft. over an E. slope.</p>
40.00	<p>The standard cor. of secs. 31 and 32, monumented with a basalt stone, 18x7x7 ins., plainly mkd. with 5 notches on the E. edge, 1 notch on W. edge and SC on the N. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C</p> <p>T41N R54E</p> <p>S 31 S 32</p> <hr style="width: 50px; margin: 0 auto;"/> </div> <p>1976</p> <p>bury the original cornerstone alongside the iron post.</p>
	<p>N. 89° 35' W., along the S. bdy. of sec. 31.</p> <p>Over mountainous land, through sagebrush and scattered aspen; asc. 40 ft. over an E. slope.</p> <p>7.00 Spur, slopes NE.; asc. 40 ft. over a rolling N. slope.</p> <p>33.20 Trail road, bears NW. and SE.; asc. 20 ft. over an E. slope.</p> <p>37.12 Point for the N. ¼ sec. cor. of sec. 6, at proportionate distance.</p>