

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 N., R. 54 E., MDM, NEVADA

CHAINS		
	From the cor. of secs. 5, 6, 7 and 8.	
	N. 0° 12' E., bet. secs. 5 and 6.	
	Over gently rolling land, through sagebrush.	
2.00	Trail road, bears ENE. and WSW.	
20.17	Point for the S. 1/16 sec. cor. of secs. 5 and 6.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.	
	<p style="text-align: center;">T41N R54E S1/16 S 6 S 5</p>	
	<p style="text-align: center;">1976</p>	
	Ascend 40 ft. over a SE. slope.	
40.34	The ¼ sec. cor. of secs. 5 and 6, monumented with a quartzite stone, 16x12x8 ins., plainly mkd. ¼ on the W. face, firmly set in a mound of stone.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.	
	<p style="text-align: center;">T41N R54E ¼ S 6 S 5</p>	
	<p style="text-align: center;">1976</p>	
	bury the original cornerstone alongside the iron post.	
	<p style="text-align: center;">_____</p>	
	N. 0° 17' W., beginning new measurement.	
	Over gently rolling land; asc. 40 ft. over a SE. slope.	
19.64	Point for the N. 1/16 sec. cor. of secs. 5 and 6.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.	
	<p style="text-align: center;">T41N R54E N1/16 S 6 S 5</p>	
	<p style="text-align: center;">1976</p>	
31.30	Pratt Creek, 20 lks. wide, 2 ft. deep, course SE.; asc. 10 ft. over a SE. slope.	
34.76	Intersect the S. bdy. of sec. 31, T. 42 N., R. 54 E.	