

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 43 N., R. 54 E., MDM, NEVADA

CHAINS

67.00

Spur, slopes ENE.; desc. 80 ft. over a N. slope.

79.44

The cor. of Tps. 43 and 44 N., Rs. 54 and 55 E., monumented with a basalt stone, 16x16x18 ins., mkd. with 6 notches on N. and S. edges and 6 grooves on E. and W. faces, firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock with a mound of stone, 4 ft. base to top, with brass cap mkd.

T44N
R54E R55E
S 36 | S 31
S 1 | S 6
T43N

1976

bury the original cornerstone alongside the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors, A.J. Hatch and J.H. Eaton, in 1870, and the Survey and Resurvey Executed by U.S. Deputy Surveyor H.B. Maxson, in 1900.

The cor. of secs. 11, 12, 13 and 14, monumented with a basalt stone, 8x6x4 ins., firmly set and exposed 4 ins. above ground. No marks found. This stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T43N R54E
S 11 | S 12
S 14 | S 13

1976

bury the unmarked stone and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.

N. 0° 42' E., over nearly level meadow land.

4.00

Fence, bears E. and W.

4.40

Small Creek, 10 lks. wide, 1 ft. deep, course ESE.