

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 68 E., MDM, NEVADA

CHAINS

Set an aluminum post, 30 ins. long, 2½ ins. diam.,
8 ins. in the ground to bedrock and in a mound of
stone, 4 ft. base to top, with brass cap mkd.

T30N R68E

¼

S 4|S 3

1977

from this corner

A pine, 14 ins. diam., bears N. 85½° E., 44 lks.
dist., mkd. T30N R68E ¼ S 3 BT.

A pine, 14 ins. diam., bears N. 64 ¾° W.,
25 lks. dist., mkd. T30N R68E ¼ S 4 BT.

U.S.C. & G.S. triangulation station GOSHUTE,
monumented with a standard bronze disk set flush
in bedrock, bears S. 21° 25' E., 6.03 chs. dist.

Descend 520 ft. over broken NW. slope.

80.00

Point for the 80 1/16 sec. cor. of secs. 3 and 4.

Set an aluminum post, 30 ins. long, 2½ ins. diam.,
16 ins. in the ground to bedrock and in a mound of
stone, 3 ft. base to top, with aluminum cap mkd.

T30N R68E

1/16

S 4|S 3

80

1977

from this corner

A fir, 10 ins. diam., bears N. 33½° E., 21 lks.
dist., mkd. T30N R68E 80 1/16 S 3 BT.

A fir, 18 ins. diam., bears N. 51½° W., 20 lks.
dist., mkd. T30N R68E 80 1/16 S 4 BT.

Desc. 60 ft. over NW. slope.

93.18

Intersect the Sixth Standard Parallel North.

Point for the closing cor. of secs. 3 and 4.

Set an aluminum post, 30 ins. long, 2½ ins. diam., on
solid rock and over a cross (X) and in a mound of stone,
4 ft. base to top, with aluminum cap mkd.