

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 68 E., MDM, NEVADA

CHAINS
96.73

Intersect the Sixth Standard Parallel North.

Point for the closing corner of secs. 5 and 6.

Set an aluminum post, 30 ins. long, 2½ ins. diam.,
6 ins. in the ground to bedrock and in a mound of
stone, 4 ft. base to top, with aluminum cap mkd.

T31N R68E
S 31
S 6 | S 5
CC
T30N R68E

1977

From this corner, the standard ¼ sec. cor. of sec. 31,
T. 31 N., R. 68 E., monumented with an iron post, 1 in.
diam., firmly set in a mound of stone, with brass cap
mkd. as described in the field notes of the dependent
resurvey of the Sixth Standard Parallel North, through
R. 68 E., executed under Group No. 194, bears S. 88°
43' E., 9.42 chs. dist.

From this same corner, the standard cor. of Tps. 31 N.,
Rs. 67 and 68 E., monumented with an iron post, 2 ins.
diam., firmly set and exposed 9 ins. above the ground,
with brass cap mkd. as described in the field notes of
the dependent resurvey of the Sixth Standard Parallel
North, through R. 68 E., executed under Group No. 194,
bears N. 88° 43' W., 30.59 chs. dist.

Land, mountainous.

Soil, sandy clay loam and rocky.

Timber, fir, bristlecone pine, pinon and juniper.

Undergrowth, sagebrush, bitterbrush and bunch grass.

Point for the N. ¼ sec. cor. of sec. 5, is on the S. bdy.
of sec. 31, T. 31 N., R. 68 E., and at midpoint bet. the
closing cors.

Set an aluminum post, 30 ins. long, 2½ ins. diam.,
4 ins. in the ground to bedrock and in a mound of stone,
4 ft. base to top, with aluminum cap mkd.

¼ S 5
T30N R68E

1977

From this corner, the standard cor. of secs. 31 and 32,
T. 31 N., R. 68 E., bears S. 88° 43' E., 9.43 chs. dist.

From this same corner, the standard ¼ sec. cor. of sec.
31, T. 31 N., R. 68 E., bears N. 88° 43' W., 30.58 chs.
dist.