

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF RANGE 53 EAST

CHAINS		
	<p style="text-align: center;">T41N R53E S 32 S 6   S 5 T40N   R53E C C</p> <p style="text-align: center;">1976</p>	
38.00	Ridge, bears NNE. and SSW.	
39.56	<p>The standard cor. of secs. 31 and 32, monumented with a mound of stone. No marked stone found. This position is harmoniously related to existing marked corners and is accepted as the best available evidence of the position of the corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T41N R53E S 31   S 32</p> <p style="text-align: center;">1976</p> <p>raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.</p>	
	<p>N. 89° 31' W., along the S. bdy. of sec. 31.</p> <p>Over mountainous land, covered with sagebrush; desc. 600 ft. over a W. slope to the standard ¼ sec. cor. of sec. 31.</p>	
5.30	Fence, bears S. 53° W. and N. 53° E., 0.66 chs. dist. to fence cor., from which fences bears N. 53° E., S. 53° W. and W.; along fence.	
34.82	<p>Point for the N. ¼ sec. cor. of sec. 6, T. 40 N., R. 53 E., is at proportionate distance and on the Eighth Standard Parallel North.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">¼ S 6 T40N R53E</p> <p style="text-align: center;">1976</p> <p>set a wooden fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>	
39.54	The standard ¼ sec. cor. of sec. 31, monumented with a limestone, 12x6x6 ins., mkd. ¼ on N. face and firmly set in a mound of stone.	