

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 41 N., R. 52 E., MDM, NEVADA

CHAINS	
	<p>N. 0° 19' E., along the E. bdy. of sec. 12.</p> <p>Over rolling land, covered with sagebrush; along fence.</p>
38.13	<p>Point for the W. <math>\frac{1}{4}</math> sec. cor. of sec. 7, T. 41 N., R. 53 E., on the E. bdy. of sec. 12, T. 41 N., R. 52 E., and at midpoint in latitude on the W. bdy. of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T41N  R53E   <math>\frac{1}{4}</math>  S 7</p> <p style="text-align: center;">1976</p>
40.21	<p>raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of sec. 12, monumented with a quartzite stone, 20x8x6 ins., mkd. <math>\frac{1}{4}</math> on the W. face and firmly set 12 ins. in the ground, with a mound of stone W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N  R52E  <math>\frac{1}{4}</math>   S 12 </p> <p style="text-align: center;">1976</p>
	<p>bury the marked stone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>This corner is located 37 lks. W. of a fence, bearing N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 18' E., beginning new measurement.</p> <p>Over rolling land, covered with sagebrush; along fence.</p>
15.00	Marsh Creek, 80 lks. wide, 1 ft. deep, course NW.
16.00	Trail road, bears NW. and SE.
31.00	Spur, slopes W.
37.54	<p>The closing corner of secs. 6 and 7, T. 41 N., R. 53 E., monumented with a quartzite stone, 22x10x8 ins., mkd. with 5 notches on the SE. edge, 1 notch on the NW. edge, CC on the E. face and firmly set 12 ins. in the ground, with a mound of stone E. of cor.</p>