DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 41 N., R. 52 E., MDM, NEVADA

		T. 41 N., R. 52 E., MDM, NEVADA
	CHAINS	At the corner point
		Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T41N T41N R53E R52E <u>S 6</u> S 12 S 7 CC
		1976
		bury the original cornerstone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, E. of cor.
	41.93	The cor. of secs. 1 and 12, monumented with a quartzite stone, 22x8x6 ins., mkd. with 5 grooves on the S. face and 1 groove on the N. face and firmly set 20 ins. in the ground.
		At the corner point
		Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T41N R52E T41N S 1 R53E S 12 S 6
		1976
		bury the marked stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
		This corner is located 55 lks. W. of a fence bearing N. and S.
		N. 0° 08' E., along the E. bdy. of sec. 1.
		Over rolling land, covered with sagebrush; along fence.
	0.70	Creek, 5 lks. wide, 1 ft. deep, course SW.
	9.20	Spur, slopes SW.
	19.00	Draw, drains SW.
	35.74	Point for the W. ¼ sec. cor. of sec. 6, T. 41 N., R. 53 E., on the E. bdy. of sec. 1, T. 41 N., R. 52 E. is at proportionate distance on the W. bdy. of sec. 6.
		Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
1	i	