

DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 42 N., R. 52 E., MDM, NEVADA

CHAINS	
22.40	<p>Point for the W. $\frac{1}{4}$ sec. cor. of sec. 7, T. 42 N., R. 53 E., is on the E. bdy. of sec. 12 and at midpoint between the closing corners.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div>T42N R53E $\frac{1}{4}$ S 7</div> <p>1977</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>Ascend 200 ft. over a S. slope.</p>
38.24	<p>The $\frac{1}{4}$ sec. cor. of sec. 12, monumented with a slate stone, 12x8x4 ins., mkd. $\frac{1}{4}$ on the W. face, firmly set $\frac{1}{4}$ ins. in the ground, with a mound of stone, W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div>T42N R52E $\frac{1}{4}$ S 12</div> <p>1977</p> <p>bury the original cornerstone alongside the iron post.</p> <hr/> <p>N. $1^{\circ} 11'$ W., beginning new measurement.</p> <p>Over mountainous land, covered with sagebrush; asc. 10 ft. over a SE. slope.</p>
0.50	<p>Spur, slopes SE.; over an E. slope.</p>
5.00	<p>Draw, drains SE.; asc. 30 ft. over a S. slope.</p>
11.00	<p>Saddle on ridge, bears NE. and SW.; desc. 200 ft. over a NW. slope.</p>
23.97	<p>The closing cor. of secs. 6 and 7, T. 42 N., R. 53 E., monumented with a slate stone, 15x10x10 ins., mkd. with 5 grooves on the S. face, 1 groove on the N. face and CC on the E. face, firmly set 6 ins. in the ground.</p>