

DEPENDENT RESURVEY OF THE EAST BOUNDARY  
T. 43 N., R. 52 E., MDM, NEVADA

CHAINS	
50.00	Creek, 20 lks. wide, 1 ft. deep, course W.
60.30	Trail road, bears W. and SE.
63.65	Point for the closing cor. of secs. 6 and 7, T. 43 N., R. 53 E., at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  $\begin{array}{c c} T43N & T43N \\ R52E & R53E \\ \hline S & 6 \\ S & 7 \end{array} \text{ CC}$ <p style="text-align: center;">1977</p> set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
63.80	Spring branch, 10 lks. wide, ½ ft. deep, flows irregularly S.  Ascend 80 ft. over a SW. slope.
80.76	The cor. of secs. 1 and 12, monumented with a basalt stone, 17x8x5 ins., mkd. with 5 notches on the S. edge and 1 notch on the N. edge, firmly set 8 ins. in the ground, with a mound of stone, W. of cor.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.  $\begin{array}{c c} T43N & T43N \\ R52E & R53E \\ \hline S & 1 \\ S & 12 \end{array} \text{ S } 6$ <p style="text-align: center;">1977</p> bury the original cornerstone and set a steel fence post, 6 ft. long, 14 ins. in the ground, alongside the iron post.
2.855	N. 0° 03' E., along the E. bdy. of sec. 1.  Over mountainous land, covered with sagebrush; asc. 10 ft. over a SW. slope.  Point for the S. 1/16 sec. cor. of sec. 6, T. 43 N., R. 53 E.