

Dependent Resurvey, Portion, W. Bdy.,  
T. 33 N., R. 56 E., Mt. Diablo Mer., Nevada

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 33 N R 55 E R 56 E           ½ S 24   S 19 1976</p>	
	<p>Set a 6 ft. steel fence post alongside the iron post.</p>	
	<p>This cor. falls 44 lks. W. of barbed wire fence, bears N. and S.</p>	
48.10	<p>Barbed wire fence, 5 strands, bears E., 40 lks. to cor. of fences extending N., S., and W.</p>	
80.76	<p>The cor. of secs. 13, 18, 19, and 24, determined at the intersection of barbed wire fences, 5 strands, extending S. and W. This position has long been recognized by local landowners as the cor. and is accepted as the best available evidence of the original cor. position.</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, 2½ ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T 33 N R 55 E R 56 E   S 13   S 18   S 24   S 19 1976</p>	
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 N., R. 56 E., Mount Diablo Meridian, Nevada</p>	
	<p style="text-align: center;">(Restoring a portion of the 1868 survey by C.C. Tracy, U.S. Deputy Surveyor)</p>	
	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp.</p>	
	<p>N. 0° 03' W., bet. secs. 35 and 36.</p>	
	<p>Over nearly level land, along the W. edge of a dirt road, 40 lks. wide.</p>	
39.225	<p>Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate dist. There is no remaining evidence of the original cor.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 33 N R 56 E           ½ S 35   S 36 1976</p>	