Dependent Resurvey, Portion, Subdivisional Lines, T. 33 N., R. 56 E., Mt. Diablo Mer., Nevada

CHAINS	
	T 33 N R 56 E S 16 S 15 S 21 S 22
	1972 RLS 1404 CHILTON ENG
	This monument is shown on the Chilton Engineering plat hereinbefore described, is locally recognized, and is accepted as the best available evidence of the original cor. position.
	The control line was fully retraced, and no evidence of intervening cors. was found.
	From this same point the cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., bears N. 0° 51' W., 239.74 chs. dist., monumented by persons unknown, with an iron rod, 3/8 ins. diam., firmly set, protruding 4 ins. above the ground, at the cor. of barbed wire fences, 4 strand, extending N. and W. This point is recognized by local private surveyors and landowners as the cor., and is accepted as the best available evidence of the original cor. position.
	This control line was fully retraced and no evidence of intervening cors. was found.
	N. 86° 58' W., bet. secs. 18 and 19.
	Over rolling hills, through moderate sagebrush.
1.40	Barbed wire fence, 4 strands, bears N. 10° E. and S. 10° W.
3.90	Nevada State Highway No. 46, paved, 80 lks. wide, bears N. 10° E. and S. 10° W.
6.40	Barbed wire fence, 4 strands, bears N. 10° E. and S. 10° W
39.11	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist. There is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 33 N R 56 E 1/4 S 18 S 19 1976
	Set a 6 ft. steel fence post alongside the iron post.
77.51	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp.
	Subdivision of Section 29, T. 33 N., R. 56 E., Mount Diablo Meridian, Nevada
	From the ½ sec. cor. of secs. 29 and 32.
	N. 0° 53' E., on the N. and S. center line of sec. 29.