

Dependent Resurvey, Portion Ruby Valley G.M.,
T. 12 N., R. 56 E., Mt. Diablo Mer., Nevada

CHAINS 40.44	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate dist. There is no remaining evidence of the original cor. This cor. now refers to sec. 6 only.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td style="border-left: 1px solid black; padding-left: 5px;">T 12 N</td></tr> <tr><td style="border-left: 1px solid black; padding-left: 5px;">R 56 E</td></tr> <tr><td style="border-left: 1px solid black; padding-left: 5px;">$\frac{1}{4}$</td></tr> <tr><td style="border-left: 1px solid black; padding-left: 5px;">S 6</td></tr> </table> <p>1976</p> </div> <p>Set a 6 ft. steel fence post alongside the iron post.</p> <p>This cor. falls in a crested wheat grass field.</p>	T 12 N	R 56 E	$\frac{1}{4}$	S 6		
T 12 N							
R 56 E							
$\frac{1}{4}$							
S 6							
60.70	Barbed wire fence, 4 strands, extending E. and W.; leave crested wheat grass field, edge bears same.						
61.10	Road, gravel, 25 lks. wide, bears E. and W.						
80.50	Irrigation ditch, 8 lks. wide, 2 ft. deep, course S. 60° W.						
80.88	The cor. of Tps. 12 and 13 N., R. 56 E., described in the field notes of the dependent resurvey of a portion of the Ruby Valley Guide Meridian, T. 13 N., R. 56 E., of this assignment.						
<hr/> Dependent Resurvey of a Portion of the Subdivisional Lines of T. 12 N., R. 56 E., Mount Diablo Meridian, Nevada <hr/>							
<hr/> Restoring the 1870 survey by E. B. Monroe <hr/>							
<p>From the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented with a mound of stone, 3 ft. base, 1 ft. high; no mkd. stone found. This mound is harmoniously related to identified original cors. and is accepted as the best available evidence of the original cor.</p>							
At the cor. point							
<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground, to solid rock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>							
<table style="border-collapse: collapse; margin: auto;"> <tr><td>T 12 N</td><td>R 56 E</td></tr> <tr><td>$\frac{1}{4}$</td><td>S 22</td></tr> <tr><td></td><td>S 27</td></tr> </table> <p>1976</p>		T 12 N	R 56 E	$\frac{1}{4}$	S 22		S 27
T 12 N	R 56 E						
$\frac{1}{4}$	S 22						
	S 27						
Set a 6 ft. steel fence post alongside the iron post.							
<p>From this point U.S.C. and G.S. triangulation station "IRWIN 1939" bears S. $22^\circ 59'$ E., 54.40 chs. dist., monumented with a standard brass cap, $3\frac{1}{2}$ ins. diam., firmly cemented into a drill hole in a rock outcrop, with top mkd. IRWIN 1939 and a triangle.</p>							
N. $88^\circ 52'$ W., bet. secs. 22 and 27.							
Desc. over NW. slope through moderate sagebrush.							
34.80	Nevada State Highway No. 20, paved, 50 lks. wide, bears N. 45° W. and S. 45° E.						