

Dependent Resurvey, Portion Subdivisional Lines,  
T. 12 N., R. 56 E., Mt. Diablo Mer., Nevada

## CHAINS

41.04

Point for the cor. of secs. 21, 22, 27, and 28, at proportionate position. There is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.

T 12 N	R 56 E
S 21	S 22
S 28	S 27

1976

Set a 6 ft. steel fence post alongside the iron post.

From this point the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the tp., bears S. 1°15' W., 160.67 chs. dist., monumented with a basalt stone, 15 x 10 x 10 ins., with 3 notches on NE. edge, firmly set, protruding 8 ins. above the ground in a collar of stone, 2 ft. base, 3 ins. high, with steel fence post set alongside. This control line was fully retraced and no remaining evidence of intervening cors. was found.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.

T 12 N	R 56 E
S 33	S 34
S 4	S 3

1976

Deposit the original stone alongside iron post.

Reset the 5 ft. steel fence post alongside the iron post.

N. 2°18' W., bet. secs. 21 and 22.

Over rolling hills, sloping generally W., through moderate sagebrush.

6.20

Nevada State Highway No. 20, paved, 50 lks. wide, bears N. 45° W. and S. 45° E.

40.19

The ¼ sec. cor. of secs. 21 and 22, monumented with a basalt stone, 12 x 6 x 5 ins., with chisel marks ¼ visible on E. face, loosely set, in a mound of stone, 3 ft. base, 1 ft. high.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 12 N	R 56 E
¼	
S 21	S 22

1976