

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
OF T. 20 N., R. 20 E., MDM, NEVADA

CHAINS 39.17	<p>The closing cor. of Tps. 20 N., Rs. 19 and 20 E., monumented with an iron post, 2 ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 20 N., R. 19 E., executed under Group No. 312.</p> <p>From this corner, the standard cor. of Tps. 21 N., Rs. 19 and 20 E., bears S. 89° 50' W., 6.50 chs. dist.</p>
<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF T. 20 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of a Portion of the Survey Executed under Joint Contract by U.S. Deputy Surveyors John Smyles and Andrew J. Hatch in 1872, and the Resurvey and Completion Survey Executed by U.S. Deputy Surveyor John Menardi in 1905.</p>	
<p>From the cor. of secs. 27, 28, 33 and 34, monumented with an iron pipe, 4 ins. diam., firmly set in concrete, with a 1½ in. iron pipe extending from center, and a steel fence post, firmly set and exposed 6 ft. above the ground. This position has been locally recognized as the corner and is accepted as the best existing evidence of the position of the original corner.</p>	
<p>At the corner point</p>	
<p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.</p>	
<p>T20N R20E S 28 S 27 S 33 S 34</p>	
<p>1976</p>	
<p>deposit the iron pipe and steel fence post alongside the iron post.</p>	
<p>From this corner, a power pole bears E., 9 lks. dist.; from which powerline bears N. and S.</p>	
<p>N. 0° 26' E., bet. secs. 27 and 28.</p>	
<p>Over rolling land, through scattered sagebrush; thence along W. side of powerline in a fence.</p>	
9.70	<p>Fence, bears E. and W., 2 lks. dist. to corner of fences, from which fences bear N., S. and W.; thence N. along powerline in fence.</p>
39.20	<p>Orr Ditch, drains W.</p>
39.36	<p>Powerline, bears E. and W.</p>