

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 20 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R20E ¼ S 6 S 5</p> <p style="text-align: center;">1976</p> <p>deposit the iron pipe and steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 1° 39' W., beginning new measurement.</p> <p>Over rolling land.</p>
0.16	Powerline, bears N. 58½° W. and S. 58½° E.
2.70	Wash, 20 lks. wide, 2 ft. deep, drains ESE.
20.56	<p>Point for the N. 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to cap, with brass cap mkd.</p> <p style="text-align: center;">T20N R20E N 1/16 S 6 S 5</p> <p style="text-align: center;">1976</p> <p>from this corner</p> <p style="text-align: center;">A juniper, 4 ins. diam., bears S. 45° W., 148 lks. dist., mkd. X BT.</p>
20.90	Trail road, bears WNW. and ESE.
23.90	Wash, 20 lks. wide, 2 ft. deep, drains SE.
41.43	<p>Intersect the S. bdy. of sec. 32, T. 21 N., R. 20 E.</p> <p>The closing cor. of secs. 5 and 6, monumented with a rebar, 1 in. diam., firmly set in the ground, with a steel fence post alongside. This position has been recognized as the corner and is accepted as the best existing evidence of the position of the original corner.</p> <p>At the corner point</p>