DEPENDENT	RESURVE	Y OF	$\mathtt{THE}$	NORTH	BOUNDARY,
	ת זו ר	1.0	m 1	<b>€</b> 10.11	77 7 A TO A

	T. 13 N., R. 43 E., MDM, NEVADA
CHAINS	Tl4N R43E
	½ S 31 S 6
!	Tl3N
	1976
	bury the original cornerstone alongside the iron post.
	N. 80° 37' W., beginning new measurement.
	Over gently rolling land; asc. 180 ft. over an E. slope.
37.60	The cor. of Tps. 13 and 14 N., Rs. 42 and 43 E.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES AND THE SURVEY OF THE EAST ONE-HALF MILE BETWEEN SECS. 25 AND 36, T. 13 N., R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA.
	Reestablishment of the Survey Executed by U.S. Deputy Surveyors A.J. Hatch, D.H. Barker and E.L. Bridges, in 1873.
	From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp.
	N. 2° 18' E., bet. secs. 35 and 36.
	Over nearly level land, through sagebrush.
40.03	Point for the 4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T13N R43E
	s 35  s 36
	1976
	set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
61.50	Trail road, bears E. and W., irregular.
80.06	Point for the cor. of secs. 25, 26, 35 and 36, determined latitudinally at record distance from the cor. of secs. 1, 2, 35, 36, on the S. bdy. of the Tp., and longitudinally at record distance from the cor. of secs. 26, 27, 34 and 35; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.