DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES AND THE SURVEY OF THE EAST ONE-HALF MILE BETWEEN SECS. 25 AND 36, T. 13 N., R. 43 E., MDM, NEVADA

	SECS. 2) AND 30, 1. 13 N., R. 43 E., MDM, NEVADA
CHAINS	Tl3n R43E S 26 S 25 S 35 S 36
	1976
	set a steel fence post, 6 ft. long, 22 ins. in the ground alongside the iron post.
	EAST, bet. secs. 25 and 36.
	Over nearly level land, through sagebrush.
40.00	Point for the 4 sec. cor. of secs. 25 and 36, determined at record bearing and distance from the cor. of secs. 25, 26, 35 and 36; there is no remaining evidence of the original corner.
·	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T13N R43E 4 S 25 S 36
	1976
	raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of the cor.
78.06	Point for the cor. of secs. 25 and 36, on the E. bdy. of the Tp. at the intersection of a line due East from the 4 sec. cor. of secs. 25 and 36.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	Tl3N R43E R44E <u>S 25 </u> S 36
	1976
	raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of the cor.
	From this corner, the angle point on the E. bdy. of sec. 25, bears N. 1° 06' E., 1.44 chs. dist.
	From the cor. of secs. 25, 26, 35 and 36.
	NORTH, bet. secs. 25 and 26.
	Over nearly level land, through sagebrush.
40.00	Point for the 4 sec. cor. of secs. 25 and 26, at record bearing and distance from the cor. of secs. 25, 26, 35 and 36; there is no remaining evidence of the original corner.
í	