

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY  
T. 3 S., R. 53 E., MDM, NEVADA

CHAINS	
	<p>N. 1° 51' W., along the W. bdy. of sec. 6.</p> <p>Over rolling land, through scattered sagebrush and greasewood.</p> <p>39.56 Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3S R53E   <math>\frac{1}{4}</math>   S 6</p> </div> <p style="text-align: center;">1977</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p> <p>From this corner, the (Roberts) <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, monumented with a granite stone, 8x6x4 ins., plainly mkd. <math>\frac{1}{4}</math> on W. face, firmly set and exposed 6 ins. above the ground, bears S. 20° 50' W., 19.04 chs. dist. Add the marks AM and bury the cornerstone 6 ins. below the surface of the ground.</p> <p>Desc. 70 ft. over rolling NE. slope.</p> <p>73.12 The closing cor. of Tps. 2 and 3 S., R. 52 E., hereinafter described.</p> <p>79.12 The original cor. of Tps. 2 and 3 S., R. 53 E., monumented with a granite stone, 12x4x4 ins., plainly mkd. with 6 grooves on N., S., E. and W. faces, firmly set and exposed 6 ins. above the ground in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T2S T2S   R53E S 36   S 31 R52E   S 6   T3S</p> </div> <p style="text-align: center;">1977</p> <p>bury the cornerstone and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p>