

SURVEY OF THE NORTH BOUNDARY
T. 3 S., R. 52 E., MDM, NEVADA

CHAINS									
42.00	Ravine, drains N.; asc. 190 ft. over broken W. slope.								
63.60	Ridge, bears N. and S.; desc. 160 ft. over E. slope.								
80.00	Point for the cor. of secs. 1, 2, 35 and 36, North 19.5 lks. from the tangent. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to cap, ¼ ft. base, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T2S</td><td>R52E</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T3S</td></tr> </table> <p>1977</p> </div> set a steel fence post, 5 ft. long, 10 ins. in the ground, alongside the iron post. Land, mountainous. Soil, sandy clay and rocky. Undergrowth, sagebrush.	T2S	R52E	S 35	S 36	S 2	S 1	T3S	
T2S	R52E								
S 35	S 36								
S 2	S 1								
T3S									
	EAST, bet. secs. 1 and 36, on a transit line describing the tangent, which bears S. 89° 56.7' E. Over mountainous land, through scattered undergrowth; over broken NW. slope.								
5.40	Spur, slopes NE.; desc. 560 ft. over E. slope.								
40.00	Point for the ¼ sec. cor. of secs. 1 and 36, North 23.6 lks. from the tangent. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock and in a mound of stone to cap, ¼ ft. base, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T2S</td><td>R52E</td></tr> <tr><td>¼ S 36</td><td></td></tr> <tr><td>S 1</td><td></td></tr> <tr><td colspan="2">T3S</td></tr> </table> <p>1977</p> </div> set a steel fence post, 5 ft. long, 15 ins. in the ground, alongside the iron post. Asc. 30 ft. over W. slope.	T2S	R52E	¼ S 36		S 1		T3S	
T2S	R52E								
¼ S 36									
S 1									
T3S									
53.00	Low ridge, bears N. and S.; desc. 190 ft. over E. slope.								
80.00	Point for the 80 1/16 sec. cor. of secs. 1 and 36, North 28.1 lks. from the tangent.								