

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 2 S., R. 53 E., MDM, NEVADA

CHAINS		
38.60	Wash, 20 lks. wide, 3 ft. deep, drains NE.	
40.20	<p>The original <math>\frac{1}{4}</math> sec. cor. of sec. 6, monumented with a lava stone, 8x6x2 ins., plainly mkd. <math>\frac{1}{4}</math> on W. face, firmly set and exposed 6 ins. above the ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T2S R53E   <math>\frac{1}{4}</math>   S 6</p> </div> <p>1977</p> <p>bury the cornerstone and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p> <p>From this corner, the (Roberts) <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, monumented with a lava stone, 8x7x5 ins., plainly mkd. <math>\frac{1}{4}</math> on W. face, firmly set and exposed 6 ins. above the ground, bears S. 43° 54' W., 12.94 chs. dist. Add the marks AM and bury the cornerstone 6 ins. below the surface of the ground.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 02' E., beginning new measurement.</p> <p>Over gently rolling land.</p>	
3.90	Leave sag, bears NE. and SW.	
31.80	<p>Point for the cor. of Tps. 1 and 2 S., R. 52 E.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T1S R52E T2S S 36   S 6 S 1   R53E T2S  </p> </div> <p>1977</p> <p>set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
40.51	<p>The original cor. of Tps. 1 and 2 S., R. 53 E., monumented with a granite stone, 10x6x6 ins., plainly mkd. with 6 grooves on the N., S., E. and W. faces, firmly set and exposed 6 ins. above the ground.</p> <p>At the corner point</p>	