

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 3 S., R. 54 E., MDM, NEVADA

CHAINS		
	<p>S. 89° 49' W., bet. secs. 6 and 31.</p> <p>Over gently rolling land, through scattered greasewood; asc. 120 ft. over gradual E. slope.</p> <p>40.41 The original $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a granite stone, 12x10x8 ins., firmly set in a mound of stone and exposed 8 ins. above the ground, plainly mkd. $\frac{1}{4}$ on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T2S R54E</p> <p>$\frac{1}{4}$ $\frac{S \ 31}{S \ 6}$</p> <p>T3S</p> <p>1977</p> </div> <p>bury the cornerstone and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>	
	<p>S. 89° 54' W., beginning new measurement.</p> <p>Over gently rolling land; asc. 140 ft. over gradual E. slope.</p> <p>40.17 The original cor. of Tps. 2 and 3 S., Rs. 53 and 54 E., monumented with a lava stone, 20x18x16 ins., firmly set in a mound of stone and exposed 15 ins. above the ground, plainly mkd. with 6 grooves on the N., S., E. and W. faces.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T2S</p> <p>R53E R54E</p> <p>$\frac{S \ 36}{S \ 1} \frac{S \ 31}{S \ 6}$</p> <p>T3S</p> <p>1977</p> </div> <p>bury the cornerstone and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>	