

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL SOUTH,  
THROUGH A PORTION OF RANGE 54 EAST, MDM, NEVADA.

CHAINS  
41.41

The original standard cor. of secs. 33 and 34, monumented with a sandstone, 16x10x6 ins., firmly set in a mound of stone, exposed 10 ins. above the ground, plainly mkd. with 3 notches on E. edge and 3 notches on W. edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

SC  
T4S | R54E  
S 33 | S 34

1977

bury the cornerstone and set a steel fence post, 5 ft. long, 12 ins. in the ground, alongside the iron post.

from which

The cor. of secs. 3, 4, 33 and 34, Tps. 3 and 4 S., R. 54 E., monumented with an iron post, 2½ ins. diam., exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary of T. 3 S., R. 54 E., executed under Group No. 410, bears N. 0° 06' E., 480.84 chs. dist.

GENERAL DESCRIPTION

The lines resurveyed within Township 4 South, Ranges 54 and 55 East, are over rolling land. The elevation ranges from about 5600 to 6200 ft. above sea level. The soil varies from sandy clay to rocky. The vegetation consists of sagebrush and greasewood. There is scattered juniper in the higher elevations.

Access into the Township is provided by improved and unimproved desert and trail roads.

No mineral formations of consequence were noted during the resurvey.