

INDEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL
SOUTH, THROUGH A PORTION OF R. 61 E., MDM, NEVADA

CHAINS	
46.00	Ridge, bears N. and S.
64.80	Ravine, drains S.
80.00	Point for the standard cor. of secs. 31 and 32, NORTH 1.7 lks. from the tangent.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	SC T8S R61E <u>S 31 S 32</u>
	1978
	raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor. and set a steel fence post, 5½ ft. long, alongside the iron post.
	From this corner, the (Monroe) standard cor. of secs. 31 and 32, monumented with a basalt stone, 20x12x12 ins., plainly mkd. with 5 notches on the E. edge and 1 notch on the W. edge, firmly set in a mound of stone, bears N. 22° 32' E., 4.34 chs. dist. Add the marks AM and bury the cornerstone 6 ins. below the surface of the ground.
	WEST, along the S. bdy. of sec. 31, on a transit line describing the tangent, which bears S. 89° 59.0' W.
	Over rolling land, through scattered undergrowth.
2.00	Spur, slopes SSW.
11.00	Spur, slopes SSW.
30.60	Wash, 30 lks. wide, 2 ft. deep, drains S.
40.00	Point for the standard ¼ sec. cor. of sec. 31, NORTH 3.0 lks. from the tangent.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.
	SC T8S R61E <u>¼ S 31</u>
	1978
	From this corner, the (Monroe) standard ¼ sec. cor. of sec. 31, monumented with a basalt stone, 14x8x8 ins., plainly mkd. ¼ on the N. face, firmly set in a mound of stone, bears N. 20° 35' E., 4.50 chs. dist. Add the marks AM and bury the cornerstone 6 ins. below the surface of the ground.
54.30	Wash, 40 lks. wide, 2 ft. deep, drains S.
79.50	Wash, 50 lks. wide, 2 ft. deep, drains S.