

INDEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL
SOUTH, THROUGH A PORTION OF R. 61 E., MDM, NEVADA

CHAINS

79.70

Trail road, bears irregularly N. and S.

80.00

Point for the standard cor. of Tps. 8 S., Rs. 60 and 61 E., NORTH 4.7 lks. from the tangent.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
T8S
R60E R61E
S 36 | S 31

1978

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. and set a steel fence post, 5½ ft. long, alongside the iron post.

From this corner, the (Monroe) standard Tp. cor., monumented with a basalt stone, 18x12x10 ins., plainly mkd. 6 notches on the W., N. and E. edges, firmly set in a mound of stone, bears N. 20° 51' E., 4.66 chs. dist. Add the marks AM and bury the cornerstone 6 ins. below the surface of the ground.

INDEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL
SOUTH, THROUGH RANGE 60 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

This Independent Resurvey Supersedes the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1869. A diligent search was made for the original corners and those found are described in the following field notes.

From the standard cor. of Tps. 8 S., Rs. 60 and 61 E., hereinbefore described.

WEST, along the S. bdy. of sec. 36, on a transit line describing the tangent.

Over rolling land, through scattered undergrowth.

38.50

Spur, slopes SSE.

40.00

Point for the standard ¼ sec. cor. of sec. 36, NORTH 0.2 lks. from the tangent.

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.

SC
T8S R60E
¼ S 36

1978

set a steel fence post, 5½ ft. long, alongside the iron post.