

INDEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL
SOUTH, THROUGH R. 60 E., MDM, NEVADA

CHAINS	
	<p>WEST, along the S. bdy. of sec. 31, on a transit line describing the tangent, which bears S. 89° 56.7' W.</p> <p>Over rolling land, through scattered undergrowth.</p>
40.00	<p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, NORTH, 23.2 lks. dist. from the tangent.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.</p> <p style="text-align: center;">SC T8S R60E <u>¼ S 31</u></p> <p style="text-align: center;">1978</p> <p>set a steel fence post, 5½ ft. long, alongside the iron post.</p>
	<p>From this corner, the (Monroe) standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a sandstone, 14x12x6 ins., plainly mkd. $\frac{1}{4}$ on the N. face, firmly set and exposed 9 ins. above the ground, bears N. 1° 52' E., 3.33 chs. dist. Add the marks AM and bury the cornerstone 6 ins. below the surface of the ground.</p>
45.50	<p>Wash, 70 lks. wide, 2 ft. deep, drains SSW.</p>
47.00	<p>Trail road, bears N. and S.</p>
80.00	<p>Point for the standard cor. of Tps. 8 S., Rs. 59 and 60 E., NORTH 27.6 lks. dist. from the tangent.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T8S R59E R60E <u>S 36 S 31</u></p> <p style="text-align: center;">1978</p>
	<p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. and set a steel fence post, 5½ ft. long, alongside the iron post.</p> <p>From this corner, the (Monroe) standard cor. of Tps. 8 S., Rs. 59 and 60 E., monumented with a basalt stone, 18x16x8 ins., plainly mkd. 6 notches on the N., E. and W. edges, firmly set in a mound of stone, bears N. 1° 06' E., 3.09 chs. dist. Add the marks AM and bury the cornerstone 6 ins. below the surface of the ground.</p>