

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 2 N., R. 57 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T2N R57E ¼ S 7</p> <p style="text-align: center;">1977</p> <p>bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p> <hr/> <p>N. 0° 08' E., beginning new measurement.</p> <p>Over rolling land; asc. slightly over S. slope.</p>
1.13	The ¼ sec. cor. of sec. 12, T. 2 N., R. 56 E., hereinafter described; asc. 240 ft. over S. slope.
24.20	Ridge, bears E. and W.; desc. 130 ft. over N. slope.
39.50	Bladed road, bears ESE. and WNW.
39.60	Fence, bears ESE. and WNW..
41.08	<p>The cor. of secs. 1, 6, 7 and 12, identical with cor. No. 1, H.E.S. No. 117, monumented with a granite stone, 24x8x8 ins., firmly set and exposed 16 ins. above the ground, plainly mkd. with 5 notches on S. edge, 1 notch on N. edge and an X on top.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T2N R56E R57E S 1 S 6 HES S 12 S 7 117-1</p> <p style="text-align: center;">1977</p> <p>bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 0° 08' E., bet. secs. 1 and 6.</p> <p>Over rolling land, through scattered sagebrush, juniper and pinon; asc. 80 ft. over S. slope to ridge.</p>
10.71	Cor. No. 10, H.E.S. No. 117, hereinafter described.
15.63	Cor. No. 8, H.E.S. No. 117, hereinafter described, on top of low ridge, bearing E. and W.