

DEPENDENT RESURVEY OF H.E.S. NO. 117

CHAINS

DEPENDENT RESURVEY OF H.E.S. NO. 117

Reestablishment of the Survey Executed by
F.C. Haman, U.S. Forest Ranger in 1916.

Beginning at cor. No. 1, H.E.S. No. 117, identical with the cor. of secs. 1, 6, 7 and 12, Tps. 2 N., Rs. 56 and 57 E., hereinbefore described.

Thence N. 89° 45' W.

12.85


Cor. No. 2, H.E.S. No. 117, monumented with a lava stone, 27x9x6 ins., exposed 20 ins. above ground and in a mound of stone, plainly mkd. 2-HES-117 on the NE. face and a cross (X) on top, from which the original bearing trees:

A juniper, 8 ins. diam., bears N. 55° E., 66 lks. dist., with illegible scribe marks visible on open blaze. (Record bearing N. 54° 52' E.)

A juniper, 6 ins. diam., bears S. 27¼° E., 55 lks. dist., with illegible scribe marks visible on open blaze. (Record bearing S. 27° 17' E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.



bury the cornerstone alongside the iron post.


Thence N. 16° 17' W.

83.20

Cor. No. 3, H.E.S. No. 117, monumented with a granite stone, 24x15x12 ins., firmly set and exposed 12 ins. above ground, plainly mkd. 3-HES-117 on the SE. face and a cross (X) on top.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



bury the cornerstone alongside the iron post.

Thence EAST