

## DEPENDENT RESURVEY OF H.E.S. NO. 118

CHAINS


## DEPENDENT RESURVEY OF H.E.S. NO. 118

Reestablishment of the Survey Executed by  
F.C. Haman, U.S. Forest Ranger in 1916.

Beginning at Cor. No. 1, H.E.S. No. 118, monumented with a mound of stone. No marked stone found. This point is so near record position in relation to the well marked corner No. 2 to the west, that it is accepted as the true position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, NW. of cor.


Thence N. 86° 29' W.

25.82 Cor. No. 2, H.E.S. 118, monumented with a sandstone, 35x12x10 ins., firmly set and exposed 15 ins. above ground, plainly mkd. 2-HES-118, on the N. face and a cross (X) on top, from which the only remaining original bearing tree:

A pinon, 8 ins. diam., bears N. 2° 04' E., 45 lks. dist., with illegible scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



bury the cornerstone alongside the iron post.

Thence N. 40° 10' W.

13.40 Intersect the line between secs. 11 and 12, at a point from which:

The ¼ sec. cor. of secs. 11 and 12, hereinbefore described, bears SOUTH, 12.83 chs. dist.