DEPENDENT RESURVEY OF H.E.S. NO. 153 CHAINS DEPENDENT RESURVEY OF H.E.S. NO. 153 Reestablishment of the Survey Executed by F.C. Haman, U.S. Forest Ranger in 1917. Beginning at cor. No. 1, H.E.S. No. 153, monumented with a malpais stone, 24x12x3 ins., firmly set and exposed 12 ins. above ground, plainly mkd. 1-HES-153, on NW. face and a cross (X) on top. There is no remaining evidence of the original bearing trees. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd. T2N R56E bury the cornerstone and set a steel fence post, 6 ft. long, 16 ins. in the ground, alongside the iron post. Thence WEST 1.44 Cor. No. 4, H.E.S. No. 117, hereinbefore described. 6.01 Cor. No. 3, H.E.S. No. 117, hereinbefore described. 10.99 Cor. No. 2, H.E.S. No. 153, monumented with a granite stone, 30x10x4 ins., firmly set and exposed 15 ins. above ground, plainly mkd., 2-HES-153, on NE. face and a cross (X) on top. There is no remaining evidence of the original bearing trees. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T2N R56E bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, NE. of cor. Thence N. 22° 08' W. 0.178 Intersect line between secs. 1 and 36, Tps. 2 and 3 N., R. 56 E., at a point from which: The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, Tps. 2 and 3 N., R. 56 E., hereinbefore described, bears EAST, 1.41 chs. dist.