## DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 8 N., R. 39 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 8 N., R. 39 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by Glover and Perrin, U.S. Deputy Surveyors, in 1880.

The original cor. of secs. 2, 3, 34 and 35, monumented with a granite stone, 14x10x8 ins., firmly set and exposed 8 ins. above the ground, in a mound of stone, plainly mkd., with 2 notches on the N. edge and 4 notches on the W. edge. This corner now refers to the cor. of secs. 2 and 3, only.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., on solid rock, over a cross (X) and in a mound of stone to cap,  $\frac{1}{4}$  ft. base, with brass cap mkd.

T9N R39E S 35 S 3 S 2 T8N R39E

1977

bury the cornerstone alongside the iron post.

N. 89° 42' W., along the N. bdy. of sec. 3.

Over mountainous land, through scattered sagebrush; asc. 250 ft. over E. slope to ridge.

- The closing cor. of secs. 34 and 35, T. 9 N., R. 39 E., monumented with an iron post, 2½ ins. diam., set on solid rock, over a cross (X) and in a mound of stone to cap, 5 ft. base, with brass cap mkd., as described in the field notes of the survey of a portion of the subdivisional lines of T. 9 N., R. 39 E., executed concurrently under this same group.
- Ridge, bears N. and S.; desc. 170 ft. over broken rocky W. slope.
- The original ½ sec. cor. of secs. 3 and 34, monumented with a granite stone, 16x12x6 ins., firmly set and exposed 10 ins. above the ground, in a mound of stone, plainly mkd. ½ on N. face. This corner now refers to the ½ sec. cor. of sec. 3, only.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

¼ S 3 T8N R39E

1977

bury the cornerstone alongside the iron post.