

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 N., R. 39 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 N., R. 39 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
Glover and Perrin, U.S. Deputy Surveyors,
in 1880 and 1881.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy.
of the Tp.

N. 89° 53' W., bet. secs. 1 and 12.

Over mountainous land, through scattered sagebrush,
shadscale and native grass; asc. 10 ft. over SE. slope.

1.10 Spur, slopes S.

13.70 Spur, slopes S.; desc. 700 ft. over broken and ledgy W.
slope.

39.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins.
in the ground to bedrock and in a mound of stone to cap,
4 ft. base, with brass cap mkd.

T8N R39E
 $\frac{1}{4} \frac{S \ 1}{S \ 12}$

1977

Desc. 90 ft. over W. slope to sec. cor.

57.10 Bladed road, bears N. and S.

61.10 Wash, 100 lks. wide, 3 ft. deep, drains S.

79.90 The original cor. of secs. 1, 2, 11 and 12, monumented
with a granite stone, 12x9x9 ins., firmly set and
exposed 8 ins. above the ground, in a small mound of
stone, plainly mkd. with 5 notches on S. edge and 1
notch on E. edge.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T8N R39E
 $\frac{S \ 2 \ | \ S \ 1}{S \ 11 \ | \ S \ 12}$

1977

bury the cornerstone alongside the iron post and raise
a mound of stone, 3 ft. base, 2 ft. high, W. of cor.