

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF RANGE 39 EAST, MDM, NEVADA

CHAINS	
	<p>N. 89° 34' W., along the S. bdy. of sec. 31.</p> <p>Over rolling land, through scattered greasewood; desc. 100 ft. over gradual W. slope to <math>\frac{1}{4}</math> sec. cor.</p>
36.07	<p>The N. <math>\frac{1}{4}</math> sec. cor. of sec. 6, T. 10 N., R. 39 E., hereinafter described.</p>
40.35	<p>The original standard <math>\frac{1}{4}</math> sec. cor. of sec. 31, monumented with a volcanic stone, 13x8x3 ins., firmly set and exposed 8 ins. above the ground, dimly mkd. <math>\frac{1}{4}</math> on N. face.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S C T11N R39E <u><math>\frac{1}{4}</math> S 31</u> 1977</p>
	<p>bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>N. 89° 34' W., beginning new measurement.</p> <p>Over rolling land; desc. 100 ft. over gradual W. slope to Tp. cor.</p>
33.41	<p>The original closing cor. of Tps. 10 N., Rs. 38 and 39 E., monumented with a granite stone, 16x12x9 ins., firmly set in a small mound of stone and exposed 10 ins. above the ground, plainly mkd. with 6 notches on S., E. and W. edges and CC on S. face. This corner is a tellurometer traverse station, occupied under Group No. 389, Nevada, and is at latitude 38° 46' 03.841" N. and longitude 117° 38' 38.687" W.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R39E <u>S 31</u> S 1   S 6 R38E   R39E T10N CC 1977</p>
	<p>bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>