

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 39 EAST, MDM, NEVADA

<p>CHAINS 40.35</p>	<p>The original standard cor. of Tps. 11 N., Rs. 38 and 39 E., monumented with a sandstone, 17x12x10 ins., firmly set and exposed 10 ins. above the ground, in a small mound of stone, plainly mkd. with 6 notches on the N., E. and W. edges. This corner is a tellurometer traverse station, occupied under Group No. 389, Nevada, and is at latitude $38^{\circ} 46' 03.855''$ N. and longitude $117^{\circ} 38' 44.464''$ W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T11N R38E R39E <u>S 36 S 31</u></p> <p style="text-align: center;">1977</p> <p>bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p style="text-align: center;">SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 10 N., R. 39 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>The cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set on solid rock and in a mound of stone to cap, 5 ft. base, with brass cap mkd. as described in the survey of a portion of the north boundary of T. 9 N., R. 39 E., executed concurrently under this same group.</p> <p>N. $0^{\circ} 02'$ W., bet. secs. 33 and 34.</p> <p>Over mountainous land, through scattered timber and undergrowth; asc. 250 ft. over broken S. slope.</p>
<p>40.00</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T10N R39E $\frac{1}{4}$ S 33 S 34</p> <p style="text-align: center;">1977</p> <p>Asc. 160 ft. over broken S. slope.</p>
<p>47.40</p>	<p>Rocky ridge, bears E. and W.; desc. 440 ft. over broken N. slope.</p>